


ISA 60x60x6

Indian Standard Equal Leg Angle -- IS 808 : 1989

CROSS SECTION



DIMENSIONS

Leg A	60 mm
Leg B	60 mm
Thickness (t)	6 mm
Root Radius (R1)	6.0 mm
Toe Radius (R2)	3.0 mm
Centroid Cx	16.9 mm
Centroid Cy	16.9 mm
Weight per Meter	5.4 kg/m
Cross-sectional Area	684 mm ²

SECTIONAL PROPERTIES

Property	About X-X Axis	About Y-Y Axis
Moment of Inertia	Ix = 166000 mm⁴	Iy = 166000 mm⁴
Elastic Section Modulus	Zx = 3970 mm³	Zy = 3970 mm³
Radius of Gyration	rx = 15.6 mm	ry = 15.6 mm
Centroid from Heel	Cx = 16.9 mm	Cy = 16.9 mm

AVAILABLE GRADES (IS 2062 : 2011)

Grade	Yield (MPa)	UTS (MPa)	Elongation	Application
E250 (Fe 410W)	250	410	23%	General construction
E275 (Fe 440)	275	440	22%	Commercial buildings
E350 (Fe 490)	350	490	22%	Heavy industrial, bridges
E410 (Fe 540)	410	540	20%	Heavy structural, offshore

APPLICABLE STANDARDS

IS 808 : 1989	Dimensions for hot rolled steel beam, column, channel and angle sections
IS 2062 : 2011	Hot rolled medium and high tensile structural steel
IS 1852	Tolerances for hot rolled structural steel sections